

# **SRM VALLIAMMAI ENGINEERING COLLEGE**

(An Autonomous Institution)

SRM Nagar, Kattankulathur – 603 203

**DEPARTMENT OF CIVIL ENGINEERING**

**QUESTION BANK**



**IV SEMESTER**

**1903402 - APPLIED HYDRAULIC ENGINEERING**

**Regulation – 2019**

**Academic Year 2021 – 22**

*Prepared by*

**Ms.K.SUGANYA DEVI, Assistant Professor / CIVIL**



# SRM VALLIAMMAI ENGINEERING COLLEGE

SRM Nagar, Kattankulathur – 603 203.



## DEPARTMENT OF CIVIL ENGINEERING QUESTION BANK

**SUBJECT : 1903402 - APPLIED HYDRAULIC ENGINEERING**

**SEM / YEAR: IV/ II**

### UNIT I - UNIFORM FLOW

Definition and differences between pipe flow and open channel flow - Types of Flow - Properties of open channel - Velocity distribution in open channel - Steady uniform flow: Chezy equation, Manning equation - Best hydraulic sections for uniform flow – Wide open channel - Specific energy and specific force – Critical flow – Non erodible channels.

#### PART-A

1	Define open channel flow with example.	BT-1	Remembering
2	Define uniform flow in channels.	BT-1	Remembering
3	State the critical flow.	BT-1	Remembering
4	Find the critical depth and critical velocity of a water flowing through a rectangular channel of width 5 m, when the discharge is 15 m <sup>3</sup> /s.	BT-1	Remembering
5	Define hydraulic mean depth.	BT-1	Remembering
6	List the factors affecting Manning's roughness coefficient.	BT-1	Remembering
7	Classify the various types of flow in open channels.	BT-2	Understanding
8	What are the possible types of flow in open channel with respect to space and time?	BT-2	Understanding
9	What is specific energy and what is the condition for getting only one depth for a given specific energy?	BT-2	Understanding
10	Differentiate closed conduit flow and open channel flow.	BT-2	Understanding
11	Sketch the velocity distribution in rectangular and triangular channels.	BT-3	Applying
12	What is meant by most economical section?	BT-3	Applying
13	Write the Bazin's formula for the discharge in the channel.	BT-3	Applying
14	Compare the prismatic channel with the non-prismatic channel.	BT-4	Analyzing
15	Give the relationships between Chezy's 'C' and Manning's 'n'.	BT-4	Analyzing
16	Define and distinguish between steady flow and unsteady flow.	BT-4	Analyzing
17	Compute the hydraulic mean depth of a small channel of 1m wide and 0.5m deep with water flowing at 2m/s.	BT-5	Evaluating
18	Derive the dimension of constant 'C' in chezy's formula.	BT-5	Evaluating
19	Write the flow characteristics of open channel.	BT-6	Creating
20	Write about non-erodible channels. What are the factors considered while designing non-erodible channels?	BT-6	Creating

## PART –B

1.	Calculate the specific energy of $12\text{m}^3/\text{s}$ of water flowing with a velocity of $1.5\text{m/s}$ in a rectangular channel $7.5\text{m}$ wide. Find the depth of water in the channel when the specific energy would be minimum. Identify the value of critical velocity as well as minimum specific energy?	BT-1	Remembering
2.	If $y_1$ and $y_2$ are alternate depths in a rectangular channel memorize that $y_c^3 = (2y_1^2 \cdot y_2^2) / (y_1 + y_2)$ and hence the specific energy $E = (y_1^2 + y_1 y_2 + y_2^2) / (y_1 + y_2)$ .	BT-1	Remembering
3.	A $3\text{m}$ wide rectangular channel conveys $12\text{m}^3$ of water at a depth of $2\text{m}$ . Find out Specific energy of flowing fluid, Critical depth, critical velocity and the minimum specific energy, Froude number and state whether the flow is sub-critical or super critical.	BT-1	Remembering
4.	How the flows are classified under specific energy concepts? Find the discharge through a rectangular channel of width $6\text{m}$ , having a bed slope of 1 in 1000. The depth of flow is $4\text{m}$ . Use Chezy's formula, Take $C=50$ .	BT-1	Remembering
5.	Calculate the specific energy, critical depth and velocity of the flow of $10\text{m}^3/\text{s}$ in a cement lined rectangular channel $2.5\text{m}$ wide with $2\text{m}$ depth of water. Is the given flow subcritical or supercritical?	BT-2	Understanding
6.	Derive the expression for most economical rectangular channel.	BT-2	Understanding
7.	Derive chezy's formula for discharge through channel. Write the formula to find out the constant 'C'.	BT-2	Understanding
8.	Calculate the critical depth corresponding to discharge of $7.5\text{m}^3/\text{sec}$ for the following cases. (a) Rectangular Channel of width $3\text{m}$ (b) Triangular channel with side slope 1 vertical 1.25 horizontal. (c) Trapezoidal channel of bottom width $2\text{m}$ side slope 1 vertical to 1.25 horizontal.	BT-3	Applying
9.	Determine the most economical section of rectangular channel carrying water at the rate of $400$ litres/sec The bed slope of the channel is 1 in 2000. Assume Chezy's constant $C=50$ .	BT-3	Applying
10.	A concrete lined circular channel of diameter $3\text{m}$ has a bed slope of 1 in 500. Work out the velocity and flow for conditions of Maximum velocity and Maximum discharge.	BT-4	Analyzing
11.	A trapezoidal channel with side slopes 1 to 1 has to be designed to carry $10\text{m}^3/\text{s}$ at a velocity of $2\text{ m/s}$ so that the amount of lining of concrete for bed and sides is minimum. Calculate the area of lining required for one meter length of the channel.	BT-4	Analyzing
12.	The trapezoidal section or channel has side slope 3H:4V and the slope of the bed is 1 in 2000. Find the optimum dimensions of the channel. The discharge in the channel is $0.5\text{m}^3/\text{sec}$ . Chezy's Constant 'C'= 80	BT-4	Analyzing
13.	Find the rate of water through a V-Shaped Channel. Take the Value of $C=55$ and slope of bed 1 in 2000 and the apex angle as $60^\circ$ and depth of flow = $4\text{m}$ .	BT-5	Evaluating

14.	The specific energy for 5m wide rectangular channel is 4m. The discharge of water through the channel is 19cumecs. Determine the alternate depth of flow and corresponding Froude number and also state whether the flow is sub critical or super critical.	BT-6	Creating
-----	---	------	----------

### PART – C

1.	Prove that half of the top width of a most economical trapezoidal section is equal to the length of the one of the side slopes and derive the hydraulic mean depth as half of the depth of the flow.	BT-3	Applying
2.	(i) A trapezoidal channel has a bottom width of 6m and side slopes of 2H : 1V. When the depth of flow is 1.2m, the flow is 10m <sup>3</sup> /s. What is the specific energy of flow and critical depth?(7) (ii) Find the rate of flow and conveyance for a rectangular channel 7.5m wide for uniform flow at a depth of 2.25m. The channel is having bed slope as 1 in 1000. Take Chezy's constant C=55. (8)	BT-2	Understanding
3.	Derive the expressions for the most economical depths of flow in terms of the diameter of the channel of circular cross-section for maximum velocity and for maximum discharge.	BT-4	Analyzing
4.	(i) The specific energy for a 3 m wide channel is 3 Nm/N. What is the maximum possible discharge in the channel? (7) (ii) Show that in a rectangular channel, maximum discharge occurs when the flow is critical for a given value of specific energy. (8)	BT-3	Applying

### UNIT – II: GRADUALLY VARIED FLOW

Dynamic equations of gradually varied flows – Types of flow profiles - Classifications: Computation by Direct step method and Standard step method – Control section – Break in Grade – Computation.

#### PART – A

1.	Define varied flow.	BT-1	Remembering
2.	Formulate the Dynamic equations of gradually varied flow	BT-6	Creating
3.	Classify the surface profiles in channels.	BT-2	Understanding
4.	List the assumption made in the derivation of dynamic equation for gradually varied flow.	BT-1	Remembering
5.	Classify the channel bottom slopes.	BT-4	Analyzing
6.	If the depth increases in the direction of flow what type of curve is formed?	BT-5	Evaluating
7.	What is the nature of slope of the channel if critical depth line occurs above normal depth line?	BT-2	Understanding
8.	Distinguish between gradually varied flow and rapidly varied flow in open channel.	BT-2	Analyzing
9.	Differentiate afflux and backwater curve.	BT-2	Understanding
10.	Sketch the different zones of water surface profiles in critical and mild sloped channels.	BT-1	Remembering
11.	Write down the condition for mild slope and critical slope?	BT-6	Creating
12.	Illustrate the methods used to determine the length of surface profile.	BT-3	Applying
13.	Write the expression to determine the length of the backwater curve.	BT-3	Applying

14.	Distinguish between draw down and back water curve.	BT-4	Analyzing
15.	What is meant by standard step method?	BT-4	Analyzing
16.	Write about drawdown curves.	BT-3	Applying
17.	Give the formulas related to Direct Step Method.	BT-5	Evaluating
18.	Show the various combinations of slopes and resulting GVF profiles.	BT-1	Remembering
19.	Define control section.	BT-1	Remembering
20.	What are the three methods to calculate Surface profiles in prismatic channel?	BT-1	Remembering

### PART –B

1.	Find the slope of the free water surface in a rectangular channel of width 20m, having depth of flow 5m. The discharge through the channel is 50cumecs. The bed slope of the channel is 1 in 4000. Assume Chezy's constant C as 60.	BT-1	Remembering
2.	What are the assumption made in analysis of Gradually Varied Flow? Derive the dynamic equation of the GVF.	BT-1	Remembering
3.	Classify the different surface profiles for the various bottom slope condition of a channels.	BT-2	Understanding
4.	Determine the slope of the free water surface in a rectangular channel of width 20m, having depth of flow 5m. The discharge through the channel is 52 cumecs. The bed slope of the channel is 1 in 4000. Assume chezy's constant c as 60.	BT-3	Applying
5.	Explain the various types of channel slopes with neat sketches and also write down the various curves formed in each slope.	BT-4	Analyzing
6.	Briefly explain profile determination by numerical method.	BT-3	Applying
7.	Explain in details about Various combinations of slopes and the resulting GVF profiles with neat sketch.	BT-2	Understanding
8.	A river 100m wide and 3m deep has stable bed and vertical banks with a surface slope of 1 in 3000. Estimate the length of backwater curve produced by an afflux of 2m. Assume Manning's $n=0.035$ .	BT-1	Remembering
9.	A triangular channel with apex angle $75^\circ = 2\theta$ carries a flow of $12\text{m}^3/\text{sec}$ at a depth of flow 0.8m. If the bed slope is 0.009. Find the roughness coefficient of the channel.	BT-6	Creating
10.	A rectangular flume 2m wide discharge at the rate of $2\text{m}^3/\text{s}$ , the bed slope of the flume is 1 in 2500. At a certain section, the depth of the flow is 1m. Examine the distance of the section downstream where the depth of flow is 0.9m. Solve by single step method. Assume $N=0.014$ .	BT-4	Analyzing
11.	Explain in detail about Control section with neat sketches.	BT-2	Understanding
12.	Define backwater curve. Also derive the expression for the length of backwater curve.	BT-4	Analyzing
13.	A trapezoidal channel of bed width 3 m and side slopes 1 V: 1.5 H is carrying a flow of $10\text{ m}^3/\text{s}$ at a depth of 1.5m under uniform flow condition. The longitudinal slope of the channel is 0.001. Calculate the Manning's roughness coefficient of the channel.	BT-5	Evaluating
14.	In a rectangular channel of bed width 0.5m a hydraulic jump occurs at a point where depth of flow is 0.15m and Froude number is	BT-6	Creating

	2.5.Determine the Critical Depth, Specific energy, Subsequent depth and loss of head or energy dissipation.		
--	---	--	--

### PART-C

1.	Summarize the assumptions made in the derivation of the dynamic equation for gradually varied flow. Starting from the first principles, derive equations for the slope of the water surface in gradually varied flow with respect to channel bed.	BT-2	Understanding
2.	Categorize the flow profile by various numerical method.	BT-4	Analyzing
3.	Determine the length of the backwater curve passed by a afflux of 2m in a rectangular channel of width 40m and depth 2.5m. The slope of the bed is given as 1 in 11000. Take Manning's $N=0.03$ .	BT-1	Remembering
4.	How dynamic equation of gradually varied flow is simplified in wide rectangular channel.	BT-3	Applying

### UNIT – III: RAPIDLY VARIED FLOW

Application of the momentum equation for RVF - Hydraulic jumps - Types - Energy dissipation – Celerity – Rapidly varied unsteady flows (positive and negative surges)

#### PART - A

1.	What are surges in an open channel flow? State the types.	BT-1	Remembering
2.	Define : Impulse momentum principle.	BT-1	Remembering
3.	State the flow conditions for the occurrence of hydraulic jump.	BT-1	Remembering
4.	Define celerity of surge.	BT-1	Remembering
5.	List the assumptions made in the analysis of hydraulic jump using the momentum equation.	BT-1	Remembering
6.	What is the cause of surge to occur in a flow?	BT-1	Remembering
7.	Why momentum equation only used for rapidly varied flow problems.	BT-2	Understanding
8.	Describe the rapidly varied flow with example.	BT-2	Understanding
9.	What is meant by energy dissipation?	BT-2	Understanding
10.	What are the classifications of hydraulic jump?	BT-2	Understanding
11.	What are the applications of momentum equation for RVF?	BT-3	Applying
12.	Describe the uses of formation of hydraulic jump in a channel.	BT-3	Applying
13.	What is meant by positive surge?	BT-3	Applying
14.	Write the head loss equation for Hydraulic jump.	BT-4	Analyzing
15.	Differentiate the positive and negative surges?	BT-4	Analyzing
16.	Justify the transition in open channel.	BT-5	Evaluating
17.	Write down the application of transition.	BT-5	Evaluating
18.	What is the state of flow after formation of a hydraulic jump?	BT-6	Creating
19.	Discuss about the negative surge.	BT-6	Creating
20.	Write the ranges of Froude number before and after the hydraulic jump?	BT-4	Analyzing

#### PART – B

1.	In a rectangular channel of bed width 0.5 m, a hydraulic jump occurs at a point where depth of flow is 0.15 m and Froude's number is 2.5. Calculate The specific energy, The critical depth, The subsequent depths, Loss of head and Energy dissipated.	BT-2	Understanding
2.	Froude number before the jump is 10.0 in a hydraulic jump occurring in a rectangular channel and the energy loss is 3.20m. Discuss the (i) Sequent depths and (ii) The discharge.	BT-2	Understanding
3.	A rectangular channel 6m wide discharge 1200 litres/sec of water into a 6m wide apron with no slope and with a mean velocity of 6m/s. what is the height of the jump? How much energy is absorbed in the jump?	BT-3	Analyzing
4.	The depth of flow of water at a certain section of rectangular channel 2m wide is 0.3 m. The discharge through a channel is 1.5 m <sup>3</sup> /s. Determine whether a hydraulic jump will occur, if so, determine its height and loss of energy per kg.of water.	BT-4	Analyzing
5.	What is transition? How transitions are made in open channel? Also give its applications.	BT-3	Applying
6.	During an experiment conducted on a hydraulic jump, in a rectangular open channel 0.5m wide, the depth of water changes from 0.2m to 0.5m. Determine the discharge in the channel and the loss of head due to the formation of hydraulic jump.	BT-1	Remembering
7.	Define surges. What are its types? How the energy dissipated? Explain in detail.	BT-1	Remembering
8.	Explain the classification of hydraulic jumps. Write the expression for depth of hydraulic jump.	BT-2	Understanding
9.	A control sluice spanning the entry of a 3.0m wide rectangular channel having mild slope admit 16m <sup>3</sup> /s at a velocity of 4m/s. find whether a hydraulic jump is expected in the channel downstream from the sluice.	BT-1	Remembering
10.	A horizontal rectangular channel 4m wide carries a discharge of 16m <sup>3</sup> /sec. Determine whether a jump may occur at an initial depth of 0.5m or not? Determine the sequent depth to this initial depth. Also determine the energy lost in the jump.	BT-1	Remembering
11.	A rectangular channel carrying a supercritical flow is to be provided with a hydraulic jump type of energy dissipater. Energy loss required in the hydraulic jump is 5m and inlet Froude number is 8, determine the sequent depths.	BT-4	Analyzing
12.	Show that the loss of energy in a hydraulic jump, where $y_1$ and $y_2$ are the two conjugate depth. $\Delta E = \frac{(y_2 - y_1)^3}{4 y_1 y_2}$	BT-3	Applying
13.	In a rectangular channel given the discharge intensity $q = 1.50$ cumecs/m and the loss of energy in the jump $h_L = 2$ m, determine the two sequent depths.	BT-5	Evaluating
14.	A hydraulic jump occurs in a rectangular channel and the depths of flow before and after the jump are 0.45m and 1.8m respectively. Calculate the critical depth of flow.	BT-6	Creating

### PART-C

1.	What is a hydraulic jump? List the assumptions made in the analysis of hydraulic jump. Explain its classification.	BT-3	Applying
----	--	------	----------

2.	A venturiflume is 1.20m wide at entrance and 0.60m in the throat. Neglecting hydraulic losses in the flume, calculate the flow if the depths at the entrance and throat are 0.65m and 0.60m respectively. A hump is now installed at the throat, of height 20cm, so that a standing wave (Hydraulic jump) is formed beyond the throat. What is the increase in upstream depth when the same flow as before passes through the flume?	BT-4	Analyzing
3.	A spillway discharges a flood flow at a rate of 7.75 cumecs/m width. At the downstream horizontal apron the depth of flow was found to be 0.5 m. What tail water depth is needed to form a hydraulic jump? If a jump is formed, examine its type, length, head loss and energy loss as a percentage of the initial energy.	BT-3	Applying
4.	A rectangular channel 2m wide has a flow with a velocity 2m/sec and depth of flow 1.25m. The rate of flow at the downstream end is suddenly decreased. Such that the depth of flow is increased to 2m. Find the absolute velocity (celerity)'c' of the resulting surge and new discharge.	BT-2	Understanding

#### UNIT – IV: TURBINES

Application of momentum principles - Impact of Jet on flat, curved plates, Stationary and Moving – Classification of Turbines – Pelton wheel – Francis turbine – Kaplan turbine - Specific speed – Characteristic Curves of Turbines- Draft tube and cavitation Efficiency of turbines.

#### PART - A

1.	What is hydraulic turbine?	BT-1	Remembering
2.	A jet of water 40mm diameter with a velocity 30 m/strikes a stationary plate at its normal direction. Determine the force exerted by the jet.	BT-1	Remembering
3.	Define hydraulic efficiency	BT-1	Remembering
4.	Define specific speed and unit quantities of the turbine.	BT-1	Remembering
5.	State the impulse momentum equation.	BT-1	Remembering
6.	Define cavitation	BT-1	Remembering
7.	What is meant by penstock in a pelton wheel turbine?	BT-2	Understanding
8.	Describe the impulse turbine with example.	BT-2	Understanding
9.	What is reaction turbine? Give example.	BT-2	Understanding
10.	Write the types of draft tube.	BT-2	Understanding
11.	What are the applications of momentum principle?	BT-3	Applying
12.	Classify hydraulic turbines.	BT-3	Applying
13.	What are the uses of draft tubes	BT-3	Applying
14.	Differentiate the impulse and reaction turbine.	BT-4	Analyzing
15.	What are the types of turbine according to direction of flow through runner?	BT-4	Analyzing
16.	Differentiate the inward flow reaction turbine and outward flow reaction turbine.	BT-4	Analyzing
17.	Why draft tubes not used in impulse turbines?	BT-5	Evaluating
18.	Write the function of draft tube in turbine outlet.	BT-5	Evaluating
19.	What is the purpose of providing casing in turbine?	BT-6	Creating



20.	Write about governing of turbines?	BT-6	Creating
-----	------------------------------------	------	----------

**PART – B**

1.	A pelton wheel working under a head of 500m produces 13000kw at 430rpm. If the efficiency of the wheel (turbine) is 85%. Determine discharge of the turbine, diameter of the runner wheel and diameter of the nozzle. Assume suitable data.	BT-1	Remembering
2.	A Pelton wheel is designed for the following specification. Shaft power = 11712kw, Head H=380m, Speed N=750rpm overall $\eta_o=86\%$ diameter of the nozzle not to exceed $(1/6)^{th}$ of the wheel dia. Determine Wheel diameter, Diameter of jet, Number of jets required. Assume coefficient of velocity $C_v=0.985$ , Speed ratio=0.45.	BT-1	Remembering
3.	Two jets strike the buckets of a Pelton wheel is having shaft power 15450kw. The diameter of jet (d) =200mm. If net head of the turbine is 400m. Find the overall efficiency.	BT-1	Remembering
4.	A inward flow reaction turbine has inlet (external) and outlet (internal) diameters as 1.2m and 0.6m respectively. The breadth at inlet is 0.25m and 0.35m at outlet at a speed of rotation of 250rpm. The relative velocity at the entrance is 3.5m/s and radial. Calculate Absolute velocity at entrance and inclination to the tangent of the runner, Discharge and Velocity of flow at Outlet.	BT-1	Remembering
5.	A Francis turbine has an inlet diameter of 2m and outlet diameter 1.2m. The breadth of the blades is constant at 0.2m. The runner rotates at a speed of 250rpm with a discharge $8m^3/Sec$ . The Vanes are radial at inlet and the discharge is radially outward at outlet. Calculate Angle of guide Vane at inlet ( $\alpha$ ), Blade angle at outlet ( $\phi$ ).	BT-2	Understanding
6.	(i)Classify the turbines based on : (6) 1. Action of water on turbine blades 2. Head on turbine 3. Direction of flow through turbine runner 4. Specific speed 5. Disposition of turbines shaft (ii) Distinguish between impulse turbine and reaction turbine.(7)	BT-2	Understanding
7.	The external and internal diameter of an inward flow reaction turbine are 1.2m and 0.6m respectively. The head on the turbine is 22m and the velocity of the flow through the runner is constant is equal to 2.5m/sec. the guide blade angle is given as $10^\circ$ and the runner vanes are radial at inlet. If the discharge at outlet is radial determine speed of the turbine, the vane angle at the outlet of the runner and the hydraulic efficiency.	BT-2	Understanding
8.	A jet of water 30mm diameter strikes a hinged square plate at its centre with a velocity of 20m/s. The plate is deflected through at an angle of $20^\circ$ . Calculate the weight of the plate and If the plate is not allowed to swing, what will be the force required to the lower edge of the plate to	BT-3	Applying

	keep the plate in vertical position?		
9.	An inward flow reaction turbine is supplied water at the rate of 0.60 cumecs at a velocity of flow of 6 m/s. The velocity of periphery and velocity of whirl at inlet is 24 m/s and 18 m/s respectively. Assuming the discharge to be radial at outlet and Velocity of flow to be constant, determine the Vane angle at inlet and Head of water on the wheel	BT-3	Applying
10.	A Pelton wheel is to develop 13250 kW under a net head of 800m, while running at a speed of 600 rpm. If the coefficient of the jet is 0.97, speed ratio is 0.46, jet diameter is 1/15 of wheel diameter. Assuming overall efficiency as 85%, identify the Diameter of the jet ,Diameter of the wheel, Discharge and Number of jets .w	BT-4	Analyzing
11.	An inward flow reaction turbine running at 500rpm has an external diameter 70cm and a width of 18cm. if the guide vanes are at $20^{\circ}$ to the wheel tangent and absolute velocity of water at inlet is 25m/sec. Find discharge of the turbine(Q) and the runner vane angle at inlet ( $\theta$ ).	BT-4	Analyzing
12.	A Kaplan turbine develops 20,000Kw at a head of 35m and at a rotational speed of 420rpm. The outer diameter of the blades is 2.5m and the hub diameter is 0.85m. If the overall efficiency is 85% and the hydraulic efficiency is 88%, calculate the discharge, the inlet flow angle and the blade at the inlet.	BT-4	Analyzing
13.	An inward flow reaction turbine has outer and inner diameter has 1m and 0.5m respectively. The vanes are radial at inlet and the discharge is radial at outlet. The water enters the vane at an angle of $10^{\circ}$ . Assuming the velocity of flow is constant and equal to 3m/sec. Find Speed of the wheel and Vane angle at Outlet.	BT-5	Evaluating
14.	Define Draft tube and write its function. Explain the various types of draft tubes.	BT-6	Creating

### PART-C

1.	A Pelton wheel has a mean bucket speed of 10m/s with a jet of water flowing at rate of 700 litres/s under a head of 30m. The bucket deflects the jet through an angle ( $\theta$ ) $160^{\circ}$ . Calculate power given by water to the runner and the hydraulic efficiency of turbine. Assume $C_v=0.98$ .	BT-1	Remembering
2.	A Kaplan turbine develops 0.9MW under a net head of 7.5m. Speed ratio ( $v/V$ ) and flow ratio ( $V_f/V$ ) is 2.2 and 0.66 respectively. The diameter of the boss or Hub is 0.35 times the diameter of the runner. The overall efficiency is 86%. Determine the runner diameter (D), diameter of boss (d), Speed and Specific Speed of turbine.	BT-2	Understanding
3.	A Straight Conical draft tube with inlet diameter 50cm and exit diameter 90cm is of 4m height. The tube is immersed to about 1m in water. The water enters the draft tube with a velocity of 5m/sec. Taking friction head loss is 20% of velocity head at entry. Find the pressure head at the entry, draft tube efficiency and power lost in friction.	BT-3	Applying
4.	Explain the various efficiencies of hydraulic turbines.	BT-4	Analyzing

## UNIT – V : PUMPS

Classification of Pumps - Centrifugal pumps – Work done - Minimum speed to start the pump - NPSH - Multistage pumps – Characteristics curve - Reciprocating pumps - Negative slip - Indicator diagrams and its variations.

### PART - A

1.	What is meant by priming of pumps?	BT-1	Remembering
2.	What is net positive suction head in a centrifugal pump?	BT-1	Remembering
3.	Define specific speed of pump.	BT-1	Remembering
4.	What is meant by multistage pump?	BT-1	Remembering
5.	Define cavitation in pumps.	BT-1	Remembering
6.	Define suction and delivery strokes.	BT-1	Remembering
7.	Mention the main parts of centrifugal pump.	BT-2	Understanding
8.	List the types of impellers and casing for a centrifugal pump.	BT-2	Understanding
9.	What are the types of characteristic curves?	BT-2	Understanding
10.	Define slip of reciprocating pump.	BT-2	Understanding
11.	What is the role of a volute chamber of a centrifugal pump?	BT-3	Applying
12.	Mention the main components of reciprocating pump.	BT-3	Applying
13.	What is indicator diagram with sketch?	BT-3	Applying
14.	Differentiate pump and turbine.	BT-4	Analyzing
15.	What are the advantages of fitting air vessels in a Reciprocating Pump?	BT-4	Analyzing
16.	Distinguish the positive displacement pump and roto dynamic pump?	BT-4	Analyzing
17.	The difference between the water levels in the sump and the overhead tank is H. what is the total head to be generated by the pump for pumping the liquid?	BT-5	Evaluating
18.	Write about negative slip. How does it occur?	BT-5	Evaluating
19.	Write the equation for specific speed for pump and turbines.	BT-6	Creating
20.	What is the function of foot valve in a pump?	BT-6	Creating

### PART – B

1.	The outer diameter of an impeller of a Centrifugal pump is 400mm and outlet width 50mm. The pump is running at 800rpm and is working against a total head of 15m. The vane angle at outlet is $40^\circ$ and manometric efficiency is 75%. Determine Velocity of flow at outlet ( $V_{f2}$ ), Velocity of water leaving the vane ( $V_2$ ), Angle made by absolute velocity at outlet in the direction of motion (angle which water leaves the impeller) and Discharge (Q).	BT-1	Remembering
2.	A centrifugal pump having outer diameter equal to two times the inner diameter and running at 1000 rpm works against a total head of 40 m. The velocity of flow through the impeller is constant and equal to 2.5 m/s. The vanes are set back at an angle of 40 degrees at outlet. If the outer diameter of the impeller is 500 mm and width at outlet is 50 mm.	BT-1	Remembering

	List the following Vane angle at inlet, Work done by impeller on water per second and Manometric efficiency.		
3.	A Centrifugal pump is to discharge $0.118\text{m}^3/\text{sec}$ at speed of 1450rpm against a head of 25m. The impeller dia is 250mm. Its width at outlet is 50mm and manometric efficiency is 75%. Determine the vane angle at the outer periphery of impeller.	BT-1	Remembering
4.	A diameter of impeller of a Centrifugal pump at inlet and outlet are 30cm and 60cm respectively. The velocity of flow at outlet ( $V_{f2}$ ) is 2m/s and vane is set back at an angle of $45^\circ$ at the outlet. Determine minimum starting speed of pump if manometric efficiency is 70%.	BT-1	Remembering
5.	For a centrifugal pump the suction lift is 2m, delivery height is 30m, head lost in the suction and delivery pipes due to friction are 0.8m and 3m respectively. The diameter of both suction and delivery pipe is 5cm. Find the power of the prime motar required, if Overall efficiency is 70%. Take manometric efficiency as 85%. Also determine the negative head at the suction side and positive head at the delivery side. Actual head developed is 40m. Take the atmospheric pressure head as 10.3m of water.	BT-2	Understanding
6.	A Multistage Centrifugal pump is to be installed of lift water to head of 150m at the rate of 100litres/sec. The pump is coupled to an electric motor running at 1450rpm. Estimate the head developed per stage and no stage required, the required impeller diameter if the speed ratio based on impeller diameter is 0.9 and the power required if overall efficiency is 0.75.	BT-2	Understanding
7.	Explain the working principle of Submersible pump with its advantages and disadvantages.	BT-2	Understanding
8.	A single acting reciprocating pump running at 50 rpm delivers water at a rate of $0.01\text{m}^3/\text{sec}$ . The diameter of the piston(D) is 200mm and stroke length $L=400\text{mm}$ . Determine Theoretical discharge of the pump, Coefficient of discharge, slip and % slip of the pump and power required to drive the pump if $h_s=25\text{m}$ and $h_d=30\text{m}$		
9.	Define Cavitation? What are the effects and precautions against cavitation?	BT-3	Applying
10.	The diameter and stroke of a single acting reciprocating pump are 200 mm and 400 mm respectively. The pump runs at 60rpm and lifts 12 litres of water per second through a height of 25m. The diameter and length of delivery pipe are 150 mm and 20 m respectively. Find out Theoretical discharge and theoretical power required to run the pump, Percentage slip and acceleration head at the beginning and middle of the delivery stroke.	BT-5	Evaluating
11.	The diameter and stroke length of a single acting reciprocating pump are 50mm and 100 mm respectively. It takes the supply of water from a sump 4 m below the pump through a pipe 6 m long and 30 mm in diameter. It delivers water to a tank 15 m above the pump through a pipe 40 mm in diameter and 20m long. If separation occurs $70\text{ kN/m}^2$ below the atmospheric pressure, Report the maximum speed at which pump may be operated without separation. Assume that the piston has a simple harmonic motion.	BT-3	Applying
12.	A four stage centrifugal pump has 4 identical impeller keyed to the same shaft. The shaft is running at 400 rpm and the total manometric head	BT-4	Analyzing

	developed by the multistage pump is 40m. The discharge through the pump is 0.2m <sup>3</sup> /sec. The vanes of each impeller are having outlet angle as 45°. The width and diameter of impeller at outlet is 5cm and 60cm respectively. Find manometric efficiency.		
13.	A single acting reciprocating pump, running at 60rpm delivers 0.53m <sup>3</sup> of water per minute. The diameter of the piston is 200mm and stroke length 300mm. The suction and delivery heads are 4m and 12m respectively. Determine the theoretical discharge, coefficient of discharge, percentage of slip of the pump and power required to run the pump.	BT-6	Creating
14.	Derive the expression for the minimum starting speed of a centrifugal pump if the outer diameter of the impeller is two times the inner diameter.	BT-4	Analyzing

### PART-C

1.	Explain the working principle of centrifugal pump and its components with a neat sketch.	BT-1	Remembering
2.	A Centrifugal pump has the corresponding dimensions at the outlet are 700mm and 85mm respectively. The blades are curved backward at 30° to the tangent at exit. Assume radial entry. Calculate Theoretical head developed, Manometric efficiency, Pressure rise across the impeller, Pressure rise and loss of head in Volute Casing, Vane angle at inlet and delivers 0.4m <sup>3</sup> /sec water to a height of 130m. The impeller rotates at 1100rpm and has a diameter 350mm and width 170mm at inlet, Power required to drive the pump assuming an overall efficiency of 75%.	BT-1	Remembering
3.	Show that the pressure rise in the impeller of a centrifugal pump is given by $(V_{f1}^2 + u_2^2 - V_{f2}^2 \text{cosec}^2 \phi) / 2g$ provided the frictional and other losses in the impeller are neglected.	BT-2	Understanding
4.	Write and explain the working of Single acting and Double acting reciprocating pump with a neat sketch.	BT-2	Understanding

